

Formulario de Mecánica

Autor: Edgardo Rosas C.

1 Coordenadas Cartesianas: (x, y, z)

1.1 Cinemática

Posición:	$\vec{r} = x\hat{i} + y\hat{j} + z\hat{k}$
Velocidad:	$\vec{v} = \dot{x}\hat{i} + \dot{y}\hat{j} + \dot{z}\hat{k}$
Aceleración:	$\vec{a} = \ddot{x}\hat{i} + \ddot{y}\hat{j} + \ddot{z}\hat{k}$

1.2 Diferenciales

Línea:	$d\vec{l} = dx\hat{i} + dy\hat{j} + dz\hat{k}$
Superficie:	$d\vec{S} = dydz\hat{i} + dxdz\hat{j} + dxdy\hat{k}$
Volumen	$dV = dxdydz$

1.3 Operadores

Gradiente:	$\nabla\psi = \frac{\partial\psi}{\partial x}\hat{i} + \frac{\partial\psi}{\partial y}\hat{j} + \frac{\partial\psi}{\partial z}\hat{k}$
Divergencia:	$\nabla \cdot \vec{F} = \frac{\partial F_x}{\partial x} + \frac{\partial F_y}{\partial y} + \frac{\partial F_z}{\partial z}$
Rotor:	$\nabla \times \vec{F} = \left(\frac{\partial F_z}{\partial y} - \frac{\partial F_y}{\partial z} \right) \hat{i} + \left(\frac{\partial F_x}{\partial z} - \frac{\partial F_z}{\partial x} \right) \hat{j} + \left(\frac{\partial F_y}{\partial x} - \frac{\partial F_x}{\partial y} \right) \hat{k}$
Laplaciano:	$\nabla^2\psi = \frac{\partial^2\psi}{\partial x^2} + \frac{\partial^2\psi}{\partial y^2} + \frac{\partial^2\psi}{\partial z^2}$

1.4 Transformación de coordenadas

Cilíndricas:	$x = \rho \cos \phi$	$y = \rho \sin \phi$	$z = z$
Esféricas:	$x = r \sin \theta \cos \phi$	$y = r \sin \theta \sin \phi$	$z = r \cos \phi$

2 Coordenadas Cilíndricas: (ρ, ϕ, z)

2.1 Transformación de vectores unitarios

$$\hat{\rho} = \cos \phi \hat{i} + \sin \phi \hat{j} \quad \hat{\phi} = -\sin \phi \hat{i} + \cos \phi \hat{j} \quad \hat{k} = \hat{k}$$

2.2 Cinemática

Posición:	$\vec{r} = \rho \hat{\rho} + z \hat{k}$
Velocidad:	$\vec{v} = \dot{\rho} \hat{\rho} + \rho \dot{\phi} \hat{\phi} + \dot{z} \hat{k}$
Aceleración:	$\vec{a} = (\ddot{\rho} - \rho \dot{\phi}^2) \hat{\rho} + (2\dot{\rho}\dot{\phi} + \rho \ddot{\phi}) \hat{\phi} + \ddot{z} \hat{k}$
Aceleración:	$\vec{a} = (\ddot{\rho} - \rho \dot{\phi}^2) \hat{\rho} + \frac{1}{\rho} \frac{d}{dt} \left(\rho^2 \dot{\phi} \right) \hat{\phi} + \ddot{z} \hat{k}$

2.3 Diferenciales

Línea:	$d\vec{l} = d\rho \hat{\rho} + \rho d\phi \hat{\phi} + dz \hat{k}$
Superficie:	$d\vec{S} = \rho d\phi dz \hat{\rho} + d\rho dz \hat{\phi} + \rho d\rho d\phi \hat{k}$
Volumen:	$dV = \rho d\rho d\phi dz$

2.4 Operadores

Gradiente:	$\nabla \psi = \frac{\partial \psi}{\partial \rho} \hat{\rho} + \frac{1}{\rho} \frac{\partial \psi}{\partial \phi} \hat{\phi} + \frac{\partial \psi}{\partial z} \hat{k}$
Divergencia:	$\nabla \cdot \vec{F} = \frac{1}{\rho} \frac{\partial (\rho F_\rho)}{\partial \rho} + \frac{1}{\rho} \frac{\partial F_\phi}{\partial \phi} + \frac{\partial F_z}{\partial z}$
Rotor:	$\nabla \times \vec{F} = \left[\frac{1}{\rho} \frac{\partial F_z}{\partial \phi} - \frac{\partial F_\phi}{\partial z} \right] \hat{\rho} + \left[\frac{\partial F_\rho}{\partial z} - \frac{\partial F_z}{\partial \rho} \right] \hat{\phi} + \frac{1}{\rho} \left[\frac{\partial (\rho F_\phi)}{\partial \rho} - \frac{\partial F_\rho}{\partial \phi} \right] \hat{k}$
Laplaciano:	$\nabla^2 \psi = \frac{1}{\rho} \frac{\partial}{\partial \rho} \left(\rho \frac{\partial \psi}{\partial \rho} \right) + \frac{1}{\rho^2} \frac{\partial^2 \psi}{\partial \phi^2} + \frac{\partial^2 \psi}{\partial z^2}$

3 Coordenadas Esféricas: (r, θ, ϕ)

3.1 Transformación de vectores unitarios

$$\hat{r} = \sin \theta \cos \phi \hat{i} + \sin \theta \sin \phi \hat{j} + \cos \theta \hat{k} \quad \hat{\theta} = \cos \theta \cos \phi \hat{i} + \cos \theta \sin \phi \hat{j} - \sin \theta \hat{k} \quad \hat{\phi} = -\sin \phi \hat{i} + \cos \phi \hat{j}$$

3.2 Cinemática

Posición: $\vec{r} = r \hat{r}$

Velocidad: $\vec{v} = \dot{r} \hat{r} + r \dot{\theta} \hat{\theta} + r \dot{\phi} \sin \theta \hat{\phi}$

Aceleración: $\vec{a} = (\ddot{r} - r \dot{\theta}^2 - r \dot{\phi}^2 \sin^2 \theta) \hat{r} + (r \ddot{\theta} + 2\dot{r}\dot{\theta} - r \dot{\phi}^2 \sin \theta \cos \theta) \hat{\theta} + (r \ddot{\phi} \sin \theta + 2\dot{r}\dot{\phi} \sin \theta + 2r\dot{\phi}\dot{\theta} \cos \theta) \hat{\phi}$

Aceleración: $\vec{a} = (\ddot{r} - r \dot{\theta}^2 - r \dot{\phi}^2 \sin^2 \theta) \hat{r} + (r \ddot{\theta} + 2\dot{r}\dot{\theta} - r \dot{\phi}^2 \sin \theta \cos \theta) \hat{\theta} + \frac{1}{r \sin \theta} \frac{d}{dt} \left(r^2 \dot{\phi} \sin^2 \theta \right) \hat{\phi}$

3.3 Diferenciales

Línea	$d\vec{l} = dr \hat{r} + r d\theta \hat{\theta} + r \sin \theta d\phi \hat{\phi}$
Superficie	$d\vec{S} = r^2 \sin \theta d\theta d\phi \hat{r} + r \sin \theta dr d\phi \hat{\theta} + r dr d\theta \hat{\phi}$
Volumen	$dV = r^2 \sin \theta dr d\theta d\phi$

3.4 Operadores

Gradiente: $\nabla \psi = \frac{\partial \psi}{\partial r} \hat{r} + \frac{1}{r} \frac{\partial \psi}{\partial \theta} \hat{\theta} + \frac{1}{r \sin \theta} \frac{\partial \psi}{\partial \phi} \hat{\phi}$

Divergencia: $\nabla \cdot \vec{F} = \frac{1}{r^2} \frac{\partial (r^2 F_r)}{\partial r} + \frac{1}{r \sin \theta} \frac{\partial (\sin \theta F_\theta)}{\partial \theta} + \frac{1}{r \sin \theta} \frac{\partial F_\phi}{\partial \phi}$

Rotor: $\nabla \times \vec{F} = \frac{1}{r \sin \theta} \left[\frac{\partial (\sin \theta F_\phi)}{\partial \theta} - \frac{\partial F_\theta}{\partial \phi} \right] \hat{r} + \frac{1}{r} \left[\frac{1}{\sin \theta} \frac{\partial F_r}{\partial \phi} - \frac{\partial (r F_\phi)}{\partial r} \right] \hat{\theta} + \frac{1}{r} \left[\frac{\partial (r F_\theta)}{\partial r} - \frac{\partial F_r}{\partial \theta} \right] \hat{\phi}$

Laplaciano: $\nabla^2 \psi = \frac{1}{r^2} \frac{\partial}{\partial r} \left(r^2 \frac{\partial \psi}{\partial r} \right) + \frac{1}{r^2 \sin \theta} \frac{\partial}{\partial \theta} \left(\sin \theta \frac{\partial \psi}{\partial \theta} \right) + \frac{1}{r^2 \sin^2 \theta} \frac{\partial^2 \psi}{\partial \phi^2}$